

Weidmüller Heat Trace Connector for the process and oil industry

NEW



Weidmüller presents the new and innovative Heat Trace Connector for use in the process industry, and applications within the harsh outdoor environments in the oil industry. Our Heat Trace Connector is designed to connect heat trace MI cables securely, reliably and efficiently.

Product advantages are:

- Coaxial connector design with 360 degree coil spring interconnects approved for MIL spec applications
- Redundant sealing system providing IP67 protection class
- Vibration and corrosion proof clamping yoke elements as found in standard Weidmüller connectivity products
- Integrated grounding system
- Corrosion and impact resistant single piece housing
- Standard tooling installation and operation: flat blade screwdriver only, no crimp tool required
- CSA Class1 Division2/Zone2 approval, T6 temperature code, -50C to +60C

Canada

W Interconnections Canada Inc.
10 Spy Court
Markham, Ontario L3R 5H6
Telephone: (800) 268-4080
Facsimile: (905) 475-2798
Email: info1@weidmuller.ca
Website: www.weidmuller.ca

United States

W Interconnections, Inc.
821 Southlake Blvd.
Richmond, Virginia 23236
Telephone: (800) 849-9343
Facsimile: (804) 379-2593
Email: info@weidmuller.com
Website: www.weidmuller.com

Mexico

W Interconnections, S.A. de C.V.
Boulevard Hermanos Serdán 698
Col. San Rafael Oriente, C.P. 72029
Puebla, Pue. Mexico
Telephone: (222) 268 62 27
Facsimile: (222) 268 62 19
Website: www.weidmuller.com.mx

Heat Trace Connector

The Weidmüller Heat Trace Connector is designed to provide a maximum level of customer value:



- Designed to be used in a wide range of ambient temperatures from -50 °C to +60 °C
- The T6 temperature code allows for diverse fields of application
- Available with two-poles, 14–8 AWG, rated at 35 A, 600 V AC, plus integrated PE (ground)
- Lightweight yet robust, the connector housing is made of aluminum alloy with protective tin-plating
- Conforms to IP67 and type 6 requirements (connected as well as disconnected with cover)
- simple flat blade screwdriver release of latches
- Coaxial design allows for 360 degrees of mating flexibility (no complicated alignment or rotational movement is required during installation)
- Draw-latch on the connector exterior guarantees a secure fit as well as superior holding power
- The simple and reliable installation provides significant time and cost savings
- comes with or without a 3/4" to 1/2" NPT Reducer

Male HT – Connector

	Order No.
HDC HTC M 3/4"	1023890000
HDC HTC M 3/4" C/W 3/4" TO 1/2" ADAPTER	1023890050

Female HT – Connector

	Order No.
HDC HTC F 3/4"	1023880000
HDC HTC F 3/4" C/W 3/4" TO 1/2" ADAPTER	1023880050



Technical Data

Electrical Rated Data	
Contacts	2-pole (L1, L2) + PE (ground)
Ratings	35 ampere, 600 V AC, 50 Hz / 60 Hz
Wire	
Harmonized	2,5 mm ² – 10 mm ²
AWG	8 – 14 AWG
Torque	1.2 Nm (for the screw clamps and securing screws)
Other Characteristics	
Clamping Body	Aluminium Tin-Plated
Contacts	Brass silver-plated
Inserts	Polyamide (UL94-V0)
Gasket	FVMQ
End Cap Threads	3/4" NPT-F (female thread)
Torque	90.4Nm maximum (for the 3/4" NPT end)
Number of Mating Cycles	25 typical
Environmental Conditions	
Enclosure Ratings	Type 6, IP67
Approvals	
CSA	Class 1, Division 2 , Groups A,B,C,D, T6, Tamb -50 °C to +60 °C, Type 6 Class 1, Zone 2 ; Ex nA, IIC, T6, Tamb -50 °C to +60 °C, IP67
GOST / VDE / UL in preparation	

Accessories	Description	Material Properties	Order No.
ADAP EX 3/4NPT-1/2NPT C1D2	3/4" to 1/2" reducer	Copper-free aluminum	7940034662
HDC HTC Mounting	Mounting frame	Stainless Steel	1049370000
VG NPT 3/4" Eex-eMS	Ex cable gland IP68 - 5 bar	Brass, nickel plated	1778150000
Screwdriver non-insulated (not shown)	SD 0.8x4.0x100		9008340000
Screwdriver insulated (not shown)	SDI 0.8x4.0x100		9008400000

